

Ceresit



TAPIZOL 1125 Tapestry adhesive

CERESIT
TAPIZOL 1125_EN_13_1016



DESCRIPTION

Ceresit Tapizol 1125 is a water-based, white-color, smooth paste formulated based on PVA resins.

FEATURES & BENEFITS

- ▶ Ready to use
- ▶ Easy to apply
- ▶ Fast drying
- ▶ Good performance
- ▶ Excellent adhesion

USES

Designed to adhere tapestry with fabric or paper support to walls, ceilings or columns finished with plaster, cement-sand, plaster panels, wood, etc.

APPLICATION INSTRUCTIONS

1.Surface preparation. The surface must be dry, smooth, clean and uniform. Damaged or poorly attached paint must be removed.

If the surface has irregularities, it must be leveled or patched with mortar or plaster. It is suggested to do it with the following repair mixture, as appropriate. 3 parts of plaster, 2 parts of water and 0.5 parts of Ceresit Tapizol 1125. For mortar, the recommended ratio is 4.5 parts of sifted sand, 1.5 parts of cement, 1 part of water and 1 part of Ceresit Tapizol 1125. Application using wedge or spatula.

Note: Proportions are by volume.

Repaired surfaces must be dry and clean (dries approximately from one day to another, depending on the patching volume)

If it is a new surface, to facilitate the application and improve the results of the adhesive, apply the primer

Ceresit R 777, diluted 1 to 1 with clean water to seal the porosity of the substrate. Let it dry for 1.5 to 2 hours.

2. Application. Apply a uniform layer of Ceresit Tapizol 1125 by means of brush, wedge or unnotched trowel on the canvas to be pasted.

Paste the tapestry on the surface before adhesive dries. When Ceresit Tapizol 1125 is still wet, you will be allowed to move it by slightly moving the canvas so you can align the pattern of the tapestry.

Press and extend the tapestry with an unnotched trowel or wedge by sliding it on the canvas from the center toward the edges to avoid folds and air bubbles.

PRECAUTIONS

- Apply it on well leveled surfaces
- Do not apply on wet surfaces
- Do not mix Ceresit Tapizol 1125 with other products
- After opening the packaging, preferably use the product completely, if there is excess, it must be closed to prevent the entry of air or contamination

RECOMMENDATIONS

For use, wear rubber gloves. Keep out of the reach of children.

For further information, see safety measures in the label or the safety data sheet. The safety data sheet of the product is available at ceresit.com and ceresit.com.mx

WARNING



Warning. May cause an allergic skin reaction. May damage fertility or the unborn child. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing vapors, mist, or spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.

IF ON SKIN: Wash with plenty of water. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse. Store locked up. Dispose of contents and/or container according to Federal, State/ Provincial and local governmental regulations.

TECHNICAL DATA

VOC content	0.53 g/L
Supplied as	White creamy paste
Packaging	Can, 4 L (1.06 Gal)
Brookfield Viscosity @ 25°C (77°F) Rod No. 6 at 10 rpm. Ps	550 - 900
Solid Content	41 - 44%
Density @25°C (77°F), gr/cm ³	1.00 – 1.10
pH @25°C (77°F)	4.5 - 5.5
Toxicity	Non-toxic except when ingested
Yield	3.5 – 4 m ² /L (9.95 – 11.37 sq ft / Gal)
Flammability	Non-flammable (water-based)
Maximum Stowage	Box of 4: 8 superimposed pieces
Shelf life and storage conditions	In its original unopened packaging, it retains its properties for 12 months, keep it in cool and dry places, under roof.

Notes: Included data were obtained in lab conditions, at 24°C (75.2°F) +/- 1 and 50% of relative humidity. Data specified for application time, setting, finish, and pedestrian traffic, may vary depending on the environmental conditions and the thickness applied.

Recommendations provided in this data sheet are based on laboratory tests and our experience. Nevertheless, while the methods and conditions under which this product will be applied are beyond our control, it is advisable that users perform functional tests according to their needs. For any questions or cases not covered, consult our Technical Customer Service.



Henkel Capital S.A. de C.V.,

Boulevard Magnocentro No 8, Piso 2,
Col. Centro Urbano Interlomas,
Huixquilucan, Estado de México, CP 52760
Customer service: 01800-FESTER7 - web.fester@henkel.com
www.ceresit.com and www.ceresit.com.mx

Quality for Professionals